

Standex® Charts & Systems

Substrate Guide for Passenger Cars (Sanded and Cleaned Substrates)	S T E E L	Z I N C	A L U M I N U M S O F T	A L U M I N U M M E D/ H A R D	S E N S I T I V E S U B S T R A T E	F I B E R G L A S S	C U R E D F I N I S H	O E M E- C O A T	P O L Y E S T E R S	H A R D P L A S T I C	S O F T P L A S T I C	C A R B O N F I B E R	T E C H N I C A L D A T A S H E E T
Standex 2K EP Primer Aerosol (16181)	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	931
Standex 2K EP Primer Surfacer (16183)	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	931.1
Standex PE Spray Filler (16177)	Y ¹	Y ¹	Y ¹	Y ¹	N	Y	Y ²	Y ²	Y	N	N	N	231
Standex 1K Primer Filler (16134/16141)	Y ⁵	Y ⁵	Y ⁵	Y	N	N	Y	Y	Y	N	N	N	413
Standex Etching Adhesion Primer (16167)	Y ⁵	Y ⁵	Y ⁵	Y ⁵	N	N	Y	Y	Y	N	N	N	312
Standex Low VOC Etching Adhesion Primer (16189)	Y ⁵	Y ⁵	Y ⁵	Y ⁵	N	Y	Y	Y	Y	N	N	N	313
Standex 2K Transparent Adhesion Sealer (15048)	N ³	N ³	N ³	N ³	N	Y	Y	Y ²	Y	N	N	N	521
PF Filler (16220/16221)	N ³	N ³	N ³	N ³	Y ⁶	Y	Y	Y ²	Y	Y ^{6+/+8}	Y ^{6+/+8}	Y	9545
PF Sealer (16222/16223)	N ³	N ³	N ³	N ³	Y ⁶	Y	Y	Y ²	Y	Y ^{6+/+8}	Y ^{6+/+8}	Y	9546
Standex 2K HS System Filler (15161/16170)	N ³	N ³	N ³	N ³	Y ⁶	Y	Y	Y ²	Y	Y ⁷	Y ⁷	Y	548
Standex 2K Nonstop Primer Filler (15331/16153/16154)	Y ³	N ³	N ³	N ³	Y	Y	Y	Y ²	Y	Y ⁸	Y ⁷	Y	535
¹ Apply Standex 2K EP Primer Surfacer or 2K EP Primer Aerosol for maximum corrosion protection.					⁶ Is possible, but Standex 2K Nonstop Primer Filler is the best option.								
² Substrate must pass a 2K solvent test.					⁷ Add 30% Standex 2K Plasticiser (as a sanding system ONLY).								
³ Apply Standex Etching Adhesion Primer, 1K Primer Filler, 2K EP Primer Surfacer or 2K EP Primer Aerosol first for maximum corrosion resistance.					⁸ Add 15% Standex 2K Plasticiser when used as a wet-on-wet for VOC regulated areas.								
⁴ Refer to Standoflex® Plastic Refinishing.													
⁵ Must use a three step system with a Standex 2K filler.													

* Indicates a product is slated for deletion.